

The New PBH Baptistery Heater

The original U.L. listed **Titanium Element** Baptistery Heater has just got better!!!



Features

- Stainless Steel Heater Chamber
- **Fully Assembled**
- Thermostatically Controlled
- 1 Year Limited Warranty
- Intake & Discharge Fittings
- Plug In Accessories
- Visual Diagnostic System
- Hi-Limit Switch
- Technical Support

The Original
TITANIUM Element
Baptistry Heater

Ask about your
New Baptistery arriving
with the heater installed!!!

Available Options

- E-Z Fill System
- Automatic Drain



Models

PBH 5500—5,500 watts
PBH 11000—11,000 watts

May be used with
New or Existing Baptisteries!!!



PIEDMONT
COMPOSITES & TOOLING

Piedmont Composites and Tooling, LLC
33 Lewittes Road
Taylorsville, NC 28681
Phone: 828-632-8883

Heater Specifications

PBH 5500

Voltage: Pump 240v / Heater 240v

Amperage: 30; Breaker size 40-50A

Watts: 5,500

Recommended wire size: Consult with your local electrical code.

Pump Motor: 1/2 h.p.

Pump type: centrifugal

Plumbing Size: 1 1/2" PVC

Rate of Rise: 500 gallons from 70°f to 90°f – 7 hours

Maximum distance from pump to baptistery: 50 plumbing feet

GFCI Protected: **Must be connected to a GFCI Circuit (not included)**

Heating Indicator Light: Yes

Pump higher than water level: No

PBH 11000

Voltage: Pump 240v / Heater 240v

Amperage: 50; Breaker size 60-80A

Watts: 11,000

Recommended wire size: Consult with your local electrical code.

Pump Motor: 1/2 h.p.

Pump type: centrifugal

Plumbing Size: 1 1/2" PVC

Rate of Rise: 500 gallons from 70°f to 90°f – 4 hours

Maximum distance from pump to baptistery: 50 plumbing feet

GFCI Protected: **Must be connected to a GFCI Circuit (not included)**

Heating Indicator Light: Yes

Pump higher than water level: No

Technical Assistance Call: 828-632-8883